




### DESCRIPTION:

With high ability to withstand the shock loading of large current, JCTxx55 SCRs provide high dv/dt rate with strong resistance to electromagnetic interference. They are especially recommended for use on solid state relay, motorcycle, power charger, T-tools etc.

From all three terminals to external heatsink, JCTxx55Z provides a rated insulation voltage of 2500 V<sub>RMS</sub>, complying with UL standards (File ref: E252906).

### MAIN FEATURES

| Symbol                              | Value     | Symbol |
|-------------------------------------|-----------|--------|
| V <sub>DRM</sub> / V <sub>RRM</sub> | 1000/1200 | V      |
| I <sub>T(RMS)</sub>                 | 55        | A      |
| I <sub>GT</sub>                     | ≤50       | mA     |



### ABSOLUTE MAXIMUM RATINGS

| Parameter                                               |                                            | Symbol              | Value                 | Unit |
|---------------------------------------------------------|--------------------------------------------|---------------------|-----------------------|------|
| Storage junction temperature range                      |                                            | T <sub>stg</sub>    | -40-150               | °C   |
| Operating junction temperature range                    |                                            | T <sub>j</sub>      | -40-125               | °C   |
| Repetitive peak off-state voltage(T <sub>j</sub> =25°C) |                                            | V <sub>DRM</sub>    | 1000/1200             | V    |
| Repetitive peak reverse voltage(T <sub>j</sub> =25°C)   |                                            | V <sub>RRM</sub>    | 1000/1200             | V    |
| Non repetitive peak off-state voltage                   |                                            | V <sub>DSM</sub>    | V <sub>DRM</sub> +100 | V    |
| Non repetitive peak reverse voltage                     |                                            | V <sub>RSM</sub>    | V <sub>RRM</sub> +100 | V    |
| RMS on-state current                                    | TO-3P Ins<br>(T <sub>C</sub> =70°C)        | I <sub>T(RMS)</sub> | 55                    | A    |
|                                                         | TO-247S /TO-247J<br>(T <sub>C</sub> =75°C) |                     |                       |      |
|                                                         | TG-C (T <sub>C</sub> =73°C)                |                     |                       |      |

|                                                                     |             |      |           |
|---------------------------------------------------------------------|-------------|------|-----------|
| Non repetitive surge peak on-state current (tp=10ms)                | $I_{TSM}$   | 520  | A         |
| $I^2t$ value for fusing (tp=10ms)                                   | $I^2t$      | 1350 | $A^2s$    |
| Critical rate of rise of on-state current ( $I_G=2 \times I_{GT}$ ) | $dI/dt$     | 150  | $A/\mu s$ |
| Peak gate current                                                   | $I_{GM}$    | 5    | A         |
| Average gate power dissipation                                      | $P_{G(AV)}$ | 1    | W         |
| Peak gate power                                                     | $P_{GM}$    | 10   | W         |

**ELECTRICAL CHARACTERISTICS** ( $T_j=25^\circ C$  unless otherwise specified)

| Symbol   | Test Condition                                   | Value |      |      | Unit      |
|----------|--------------------------------------------------|-------|------|------|-----------|
|          |                                                  | MIN.  | TYP. | MAX. |           |
| $I_{GT}$ | $V_D=12V$ $R_L=33\Omega$                         | -     | -    | 50   | mA        |
| $V_{GT}$ |                                                  | -     | -    | 1.5  | V         |
| $V_{GD}$ | $V_D=V_{DRM}$ $T_j=125^\circ C$ $R_L=3.3K\Omega$ | 0.2   | -    | -    | V         |
| $I_L$    | $I_G=1.2I_{GT}$                                  | -     | -    | 150  | mA        |
| $I_H$    | $I_T=500mA$                                      | -     | -    | 120  | mA        |
| $dV/dt$  | $V_D=2/3V_{DRM}$ Gate Open $T_j=125^\circ C$     | 800   | -    | -    | $V/\mu s$ |

**STATIC CHARACTERISTICS**

| Symbol    | Parameter                   |                   | Value(MAX) | Unit    |
|-----------|-----------------------------|-------------------|------------|---------|
| $V_{TM}$  | $I_{TM}=80A$ $tp=380\mu s$  | $T_j=25^\circ C$  | 1.6        | V       |
| $I_{DRM}$ | $V_D=V_{DRM}$ $V_R=V_{RRM}$ | $T_j=25^\circ C$  | 10         | $\mu A$ |
| $I_{RRM}$ |                             | $T_j=125^\circ C$ | 6          | mA      |


**THERMAL RESISTANCES**

| Symbol        | Parameter            |                 | Value | Unit         |
|---------------|----------------------|-----------------|-------|--------------|
| $R_{th(j-c)}$ | junction to case(AC) | TO-3P Ins       | 0.65  | $^\circ C/W$ |
|               |                      | TO-247S/TO-247J | 0.6   |              |
|               |                      | TG-C            | 0.63  |              |


## ORDERING INFORMATION

|                                 |                                                                                              |           |                          |                                             |
|---------------------------------|----------------------------------------------------------------------------------------------|-----------|--------------------------|---------------------------------------------|
| <b>J</b>                        | <b>CT</b>                                                                                    | <b>12</b> | <b>55</b>                | <b>Z</b>                                    |
| JieJie Microelectronics Co.,Ltd | SCRs                                                                                         |           |                          | Z:TO-3P Ins T:TG-C<br>CS:TO-247S SJ:TO-247J |
|                                 | 10:V <sub>DRM</sub> /V <sub>RRM</sub> ≥1000V<br>12:V <sub>DRM</sub> /V <sub>RRM</sub> ≥1200V |           | I <sub>T(RMS)</sub> :55A |                                             |

## PACKAGE MECHANICAL DATA




| Ref. | Dimensions  |      |       |        |       |       |
|------|-------------|------|-------|--------|-------|-------|
|      | Millimeters |      |       | Inches |       |       |
|      | Min.        | Typ. | Max.  | Min.   | Typ.  | Max.  |
| A    | 4.40        |      | 4.60  | 0.173  |       | 0.181 |
| B    | 1.45        |      | 1.55  | 0.057  |       | 0.061 |
| C    | 14.35       |      | 15.60 | 0.565  |       | 0.614 |
| D    | 0.50        |      | 0.70  | 0.020  |       | 0.028 |
| E    | 2.70        |      | 2.90  | 0.106  |       | 0.114 |
| F    | 15.80       |      | 16.50 | 0.622  |       | 0.650 |
| G    | 20.40       |      | 21.10 | 0.803  |       | 0.831 |
| H    | 15.10       |      | 15.50 | 0.594  |       | 0.610 |
| J    | 5.40        |      | 5.65  | 0.213  |       | 0.222 |
| K    | 1.10        |      | 1.40  | 0.043  |       | 0.055 |
| L    | 1.35        |      | 1.50  | 0.053  |       | 0.059 |
| P    | 2.80        |      | 3.00  | 0.110  |       | 0.118 |
| R    |             | 4.35 |       |        | 0.171 |       |




| Ref. | Dimensions  |      |      |        |      |       |
|------|-------------|------|------|--------|------|-------|
|      | Millimeters |      |      | Inches |      |       |
|      | Min.        | Typ. | Max. | Min.   | Typ. | Max.  |
| A    | 15.1        |      | 16.1 | 0.594  |      | 0.634 |
| B    | 19.8        |      | 20.8 | 0.78   |      | 0.819 |
| C    | 13.8        |      | 14.8 | 0.543  |      | 0.583 |
| D    | 3.00        |      | 4.00 | 0.118  |      | 0.157 |
| E    | 2.75        |      | 3.35 | 0.108  |      | 0.132 |
| F    | 1.30        |      | 1.50 | 0.051  |      | 0.059 |
| G    | 5.10        |      | 5.80 | 0.201  |      | 0.228 |
| H    | 4.50        |      | 5.50 | 0.177  |      | 0.217 |
| J    | 1.45        |      | 2.15 | 0.057  |      | 0.085 |
| K    | 1.90        |      | 2.80 | 0.075  |      | 0.110 |
| L    | 0.55        |      | 0.80 | 0.022  |      | 0.031 |
| P    | 2.00        |      | 2.40 | 0.079  |      | 0.094 |

## PACKAGE MECHANICAL DATA



| Ref.      | Dimensions  |       |       |        |        |        |
|-----------|-------------|-------|-------|--------|--------|--------|
|           | Millimeters |       |       | Inches |        |        |
|           | Min.        | Typ.  | Max.  | Min.   | Typ.   | Max.   |
| A         |             |       | 39.2  |        |        | 1.543  |
| B         | 29.8        | 30.0  | 30.2  | 1.173  | 1.181  | 1.189  |
| C         |             |       | 20.2  |        |        | 0.795  |
| D         |             |       | 20.5  |        |        | 0.807  |
| E         |             |       | 21.6  |        |        | 0.85   |
| F         |             |       | 23    |        |        | 0.905  |
| G1        | Φ4.1        | Φ4.2  | Φ4.3  | Φ0.161 | Φ0.165 | Φ0.169 |
| H         |             | 10.3  |       |        | 0.406  |        |
| I         |             | 13.9  |       |        | 0.547  |        |
| J(T1,T2)  |             | 8     |       |        | 0.315  |        |
| K(T1,T2)  |             | 6.4   |       |        | 0.252  |        |
| M         | 2.7         | 3.0   | 3.3   | 0.106  | 0.118  | 0.130  |
| N         |             |       | 22.8  |        |        | 0.898  |
| O         |             | 8.2   |       |        | 0.323  |        |
| P         |             | 2.5   |       |        | 0.098  |        |
| Q         | 9.45        | 9.75  | 10.1  | 0.374  | 0.383  | 0.398  |
| R         | 7.8         | 7.95  | 8.1   | 0.307  | 0.313  | 0.319  |
| S         | 4.3         | 4.5   | 4.7   | 0.169  | 0.177  | 0.185  |
| Z(T1,T2)  | 0.78        | 0.8   | 0.85  | 0.0307 | 0.0315 | 0.0335 |
| G2(T1,T2) |             | Φ2    | Φ2.2  |        | Φ0.079 | Φ0.087 |
| G3        | Φ1.1        | Φ1.3  | Φ1.5  | Φ0.043 | Φ0.051 | Φ0.059 |
| G4        |             | Φ1.55 | Φ1.75 |        | Φ0.061 | Φ0.069 |
| a         | 2.95        | 3.15  | 3.35  | 0.116  | 0.124  | 0.132  |
| b         | 6.2         | 6.35  | 6.5   | 0.244  | 0.25   | 0.256  |
| c         | 9.35        | 9.75  | 10    | 0.368  | 0.384  | 0.393  |
| Z(GATE)   | 0.58        | 0.6   | 0.65  | 0.0228 | 0.0236 | 0.0256 |
| J(GATE)   |             | 5.6   |       |        | 0.221  |        |
| K(GATE)   |             | 4.65  |       |        | 0.183  |        |

## PACKAGE MECHANICAL DATA









TO-247J

| Ref. | Dimensions  |       |       |        |       |       |
|------|-------------|-------|-------|--------|-------|-------|
|      | Millimeters |       |       | Inches |       |       |
|      | Min.        | Typ.  | Max.  | Min.   | Typ.  | Max.  |
| A    | 15.50       | 15.80 | 16.10 | 0.610  | 0.622 | 0.634 |
| B    | 20.80       | 21.00 | 22.20 | 0.819  | 0.828 | 0.874 |
| C    | 19.70       | 20.00 | 20.30 | 0.776  | 0.787 | 0.799 |
| D    | 1.80        | 2.00  | 2.20  | 0.071  | 0.079 | 0.087 |
| E    | 1.90        | 2.10  | 2.30  | 0.075  | 0.083 | 0.091 |
| F    | 1.00        | 1.20  | 1.40  | 0.039  | 0.047 | 0.055 |
| G    |             | 5.44  |       |        | 0.214 |       |
| H    | 4.80        | 5.00  | 5.20  | 0.189  | 0.197 | 0.205 |
| J    | 1.90        | 2.00  | 2.10  | 0.075  | 0.079 | 0.083 |
| K    | 2.20        | 2.35  | 2.50  | 0.087  | 0.093 | 0.098 |
| L    | 0.41        | 0.60  | 0.79  | 0.016  | 0.024 | 0.031 |

## PACKAGE INFORMATION

| PACKAGE | OUTLINE          | TUBE (PCS) | INNER BOX (PCS) | PER CARTON       |
|---------|------------------|------------|-----------------|------------------|
| TO-3P   | TUBE             | 30         | 450             | 3,600            |
| TO-247S | TUBE             | 30         | 450             | 3,600            |
| TO-247J | TUBE             | 30         | 450             | 3,600            |
| PACKAGE | WEIGHT (PER PCS) | OUTLINE    | INNER BOX (PCS) | PER CARTON (PCS) |
| TG-C    | 21.5g            | BOX        | 80              | 720              |

**FIG.1:** Maximum power dissipation versus RMS on-state current**FIG.2:** RMS on-state current versus case temperature

**FIG.3:** Surge peak on-state current versus number of cycles**FIG.5:** Non-repetitive surge peak on-state current for a sinusoidal pulse with width  $t_p < 10\text{ms}$ , and corresponding value of  $I^2t$  ( $di/dt < 150\text{A}/\mu\text{s}$ )**FIG.4:** On-state characteristics (maximum values)**FIG.6:** Relative variations of gate trigger current, holding current and latching current versus junction temperature

Information furnished in this document is believed to be accurate and reliable.

However, Jiangsu JieJie Microelectronics Co.,Ltd assumes no responsibility for the consequences of use without consideration for such information nor use beyond it.

Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement.

Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information.

This document is the ninth version which is made in 20-Dec.-2018. This document supersedes and replaces all information previously supplied.



is a registered trademark of Jiangsu JieJie Microelectronics Co.,Ltd.

Copyright ©2018 Jiangsu JieJie Microelectronics Co.,Ltd. Printed All rights reserved.